

COMBO-D-LUX

Digital timer drain with integrated strainer

PRODUCT FEATURES

The COMBO-D-LUX is an all-in-one digital timer drain with an integrated ball valve and strainer.

The unit offers true digital time cycle programming luxury ranging from milliseconds to 99 hours.

The COMBO-D-LUX saves installation time and protects against large particles found in condensate, due to the integrated ball valve and strainer.

The unit can be shut off from the compressed air system enabling easy and safe maintenance work to be carried out.



COMMERCIAL BENEFITS

- Wide time setting range, offering you application flexibility
- Exceptionally accurate cycle timing
- Suitable for all types of compressed air systems
- Serviceable valve construction, offering you routine maintenance revenues
- Consult JORC for private labelling options

TECHNICAL ADVANTAGES

- Integrated mesh strainer for large particles
- Shut off valve incorporated
- Dual threaded inlet (1/2" and 1/4")
- Does not air-lock during operation
- Quick to service
- TEST feature (micro-switch)
- Bright digital illuminated display, offering you a visual indication of current operating cycle

COMBO-D-LUX

Digital timer drain with integrated strainer

DIMENSIONS



TECHNICAL SPECIFICATIONS

Max. compressor capacity Min./Max. system pressure Any size o - 16 bar (higher pressures available, see FLUIDRAIN-HP)

Min./Max. medium temperature 1 - 55 °C Min./Max. ambient temperature 1 - 55 °C

Supply voltage options Environmental protection Connector type (power)

Inlet/outlet connections Inlet connection height

Valve type Valve orifice Valve seals Valve serviceable Valve housing material

Test feature

12 – 230 VAC/DC 50/60 Hz. IP65 (NEMA4) DIN 43650-A

1/4" & 1/2" / 1/2" BSP or NPT Approx. 1 cm

2/2 way, direct acting 4 mm FPM Yes Brass



Dual inlet feature 1/2" & 1/4"



Visual display of current operating cycle



Digital processor, offering you exceptional time cycle accuracy



Also available in a FLUIDRAIN valve version

Timer cycle range (ON/OFF) Timer PCB Time cycle indication o.o1 second to 99 hours (both ON and OFF) SMD technology, ensuring consistency in production Bright LED illumination

JORC is NEN - EN - ISO 9001:2015 certified

Information provided herewith is believed to be accurate and reliable. However, no responsibility is assumed for its use or for any infringement of patents or rights of others, which may result from its use. In addition, JORC reserves the right to revise information without notice and without incurring any obligation.

JORC Industrial BV

Pretoriastraat 28 NL-6413 NN Heerlen The Netherlands Tel. +31 45 5242427

info@jorc.nl www.jorc.eu

Yes

