

FLUIDRAIN-COMBO-QS

Quick-to-program electronic timer drain with integrated strainer

PRODUCT FEATURES

The QUICKSET feature is a predetermined time setting applied on timer controlled condensate drains designed to automatically remove condensate from compressors, compressed air dryers and receivers - up to 20 m³/min. compressor capacity and 10 bar pressure.

The FLUIDRAIN-COMBO-QUICKSET saves installation time and protects against large particles found in condensate, thanks to the integrated ball valve strainer and the QUICKSET timer adjustability.

Simply adjust the timer according to the compressor capacity and the operating pressure – and go!



Simply select the compressor capacity and pressure!

COMMERCIAL BENEFITS

- Installation time saver thanks to the integrated shut off valve and mesh strainer
- Dual thread inlet (1/2" & 1/4"), offering installation flexibility
- Any type of compressed air system and up to 10 bar
- Serviceable valve construction, offering you routine maintenance revenues
- Consult JORC for private labelling options


TECHNICAL ADVANTAGES

- Integrated mesh strainer, offering valve and orifice protection from larger particles found in condensate
- Integrated shut off valve, offering easy shut off of the valve for routine maintenance
- Does not air-lock during operation
- TEST (micro-switch) feature

FLUIDRAIN-COMBO-QS

Quick-to-program electronic timer drain with integrated strainer

DIMENSIONS



Compact design!

TECHNICAL SPECIFICATIONS

| | |
|----------------------------|---|
| Max. compressor capacity | Any size |
| Pressure range | 0 - 10 bar (higher pressure available, see FLUIDRAIN) |
| Supply voltage options | 12 - 380 VAC/DC 50/60Hz. (please indicate) |
| Medium temperature | 1 - 55 °C |
| Ambient temperature | 1 - 55 °C |
| Timer cycle range (On/OFF) | Simply select capacity and pressure! |
| Timer PCB | SMD technology, ensuring consistency in production |
| Timer cycle indication | Bright LED illumination |
| TEST feature | Yes |
| Valve type | 2/2 way, direct acting |
| Valve orifice | 4 mm |
| Valve seals | FPM |
| Inlet/outlet connections | 1/4" & 1/2" / 1/2" BSP or NPT |
| Inlet connection height | 1 cm |
| Serviceable valve | Yes |
| Valve housing material | BRASS (Stainless steel available, see FLUIDRAIN) |
| Power connection | DIN 43650-A |
| Environmental protection | IP65 (NEMA4) |



Dual inlet feature
1/2" & 1/4"



Integrated mesh strainer

JORC is NEN - EN - ISO 9001:2015 certified

Information provided herewith is believed to be accurate and reliable. However, no responsibility is assumed for its use or for any infringement of patents or rights of others, which may result from its use. In addition, JORC reserves the right to revise information without notice and without incurring any obligation.

JORC Industrial BV
Pretoriastraat 28
NL-6413 NN Heerlen
The Netherlands

Tel. +31 45 5242427

info@jorc.nl
www.jorc.eu

